

SHARP®


FP-J80M FP-J60M

AIR PURIFIER OPERATION MANUAL




HIGH-DENSITY 25000 *

“Plasmacluster” and “Device of a cluster of grapes” are trademarks of Sharp Corporation.



* The number in this technology mark indicates an approximate number of ions supplied into air of 1 cm³, which is measured around the center of a room applicable floor area (at 1.2 m height above the floor) when the product is placed close to a wall at the MED mode setting.

A unique Combination of Air Treatment Technologies Triple Filtration System + Plasmacluster



High Density Plasmacluster 25000
The higher the PCI density is, the more effective PCI has.

HIGH-DENSITY 25000*

Triple Filtration System

TRAP DUST

Pre-filter traps dust larger than approx 240 micron particles.

DECREASES ODORS


Deodorizing filter absorbs many common household odors.

REDUCES TINY DUST, POLLEN & MOLD

HEPA filter traps 99.97% of particles as small as 0.3 microns.

Unique Airflow

Powerful air suction and unique airflow quickly and efficiently collect dust and other particles.



Faster airflow at a 20° angle collects dust at lower levels in the room for more effective cleaning.

Plasmacluster can remove static electricity and can thus prevent dust from attaching to walls and other surfaces.

Plasmacluster


By emitting a balance of positive and negative ions, Plasmacluster air treatment is a natural process.

PM2.5 Monitor

- Inform by lighting PM2.5 monitor when Sensitive Dust sensor detects microscopic dust.
- Display the value of PM2.5 in 3 digits.

Plasmacluster Ion Spot Mode

- Recommended when odor and germs adhering to sofa and curtains are concerned.
- Emits highdensity Plasmacluster Ions only in the forward directions.



Thank you for purchasing this SHARP Air Purifier.
 Please read this manual carefully before using the product.
 This manual should be kept in a safe place for handy reference.


CONTENTS

IMPORTANT SAFETY INSTRUCTIONS.....	4
PART NAMES	6
PREPARATION.....	8
OPERATION	
START/STOP	9
AUTO MODE	9
HAZE MODE.....	9
PLASMACLUSTER ION SPOT MODE.....	9
SELECTING MODE	9
ON TIMER.....	10
OFF TIMER.....	10
SELECTING DISPLAY	10
PLASMACLUSTER ION ON/OFF.....	10
CHILD LOCK.....	10
HOW TO CHANGE VARIOUS SETTING	11
Light Control / Auto Restart / Adjusting Senser Sensitivity (Light / Dust(sensitive) / Odor)	

CARE AND MAINTENANCE	
MAIN UNIT / BACK PANEL	12
HEPA FILTER / DEODORIZING FILTER.....	12
PLASMACLUSTER ION GENERATING UNIT..	12
REPLACEMENT	
HEPA FILTER / DEODORIZING FILTER.....	13
PLASMACLUSTER ION GENERATING UNIT..	13
TROUBLESHOOTING	14
SPECIFICATIONS.....	15

Please read before operating your new Air Purifier

The air purifier draws in room air through the air intake, circulates it through a Pre-Filter, a Deodorizing Filter and a HEPA Filter inside the main unit, and then discharges it through the air outlet. The HEPA Filter can remove 99.97% of dust particles as small as 0.3 microns that pass through the filter and also helps absorb odors. The Deodorizing Filter gradually absorbs odors as they pass through the filter.



Some odors absorbed by the filters will break down over time, causing additional odors. Depending on usage conditions, and especially if the main unit is used in environments significantly more severe than a normal household, these odors may become noticeable sooner than expected. If these odors persist, replace the filters. (page 13)

NOTE

- The air purifier is designed to remove air-suspended dust and the odors.
 The air purifier is not designed to remove harmful gases such as carbon monoxide contained in cigarette smoke.
 The air purifier may not completely remove an odor if the source of the odor is still present.

IMPORTANT SAFETY INSTRUCTIONS

Always follow basic safety precautions when using electrical appliances, including the following:

WARNING – Always observe the following to reduce the risk of electrical shock, fire, or injury:

- Read all instructions before using the main unit.
- Use only a 220-240 volt outlet.
- **This appliance is not intended for use by persons (including children) with reduced physical, sensory or mental capabilities, or lack of experience and knowledge, unless they have been given supervision or instruction concerning use of the appliance by a person responsible for their safety. Children should be supervised to ensure they do not play with the appliance.**
- **If the power cord is damaged, it must be replaced by the manufacturer, its service agent, a Sharp authorized Service Center or similarly qualified persons in order to avoid a hazard. Contact the nearest Service Center for any problems, adjustments, or repairs.**
- **Be sure to remove the power plug, before performing maintenance, when removing and attaching and replacing the filter and when not using for a long time. Failure to do so can cause a short circuit resulting in electrical shock or fire.**
- Do not use the main unit if the power cord or plug is damaged or if the connection to the wall outlet is loose.
- Periodically remove dust from the plug.
- Do not insert fingers or foreign objects into the air intake or air outlet.
- When removing the power plug, always hold the plug and never pull on the cord. Failure to do so can cause a short circuit resulting in electrical shock or fire.
- Be careful not to damage the power cord, it may cause electric shock, excess heat or fires.
- Do not remove the plug when your hands are wet.
- Do not place the main unit near or on hot objects, such as stoves or heaters, or where it may come into contact with steam.
- Do not operate the main unit in rooms where aerosol insecticides are present. Do not operate the main unit in rooms where there is oily residue, incense, sparks from lit cigarettes, or chemical fumes in the air. Do not operate the main unit in places where it may get wet, such as a bathroom.
- Be cautious when cleaning the main unit. Strong corrosive cleansers can damage the exterior.
- Do not expose the main unit to water. Doing so can cause a short circuit or electrical shock.

NOTE – What to do if the main unit interferes with radio or TV reception

If the air purifier interferes with radio or television reception, try one or more of the following measures:

- Adjust or reposition the receiving antenna.
- Increase the distance between the main unit and the radio or TV.
- Connect the equipment into an outlet on a circuit different from that of the radio or TV receiver.
- Consult the dealer or a qualified radio or TV technician.

CAUTIONS CONCERNING OPERATION

- Do not block the air intake or air outlet.
- Always operate the main unit in an upright position.
- Do not move the main unit when it is in operation.
- When moving the main unit, use the handles on both sides.
- If the main unit is on easily damaged flooring, an uneven surface, or thick-piled carpet, lift it up when moving.
- Do not operate the main unit without the filters properly installed.
- Do not wash and reuse the HEPA filter and the Deodorizing filter.
Doing so will not improve filter performance and can also cause electric shock or operating malfunctions.
- Clean the exterior with a soft cloth only. Do not use volatile fluids or detergents. The main unit surface may be damaged or cracked with Benzine, paint thinner or polishing powder. In addition, the sensors may malfunction as a result.
- Keep the main unit away from water.
- Do not scrub the Back Panel hard during its maintenance.

INSTALLATION GUIDELINES

- Avoid locations where the sensors are exposed to direct wind.
Doing so can cause the main unit to malfunction.
- Avoid locations where furniture, fabrics, or other objects can come in contact with the main unit and interfere with the intake and outtake of air.
- Avoid locations where the main unit is exposed to condensation or drastic changes in temperature. Appropriate room temperature is between 0 – 35 °C.
- Place the main unit on a level and stable surface with sufficient air circulation. When placed on heavy carpet, the main unit may vibrate slightly.
- Avoid locations that generate grease or oily smoke.
Doing so can cause the main unit exterior to crack and the sensors to malfunction.
- The dust collecting ability of the main unit is effective even when the main unit is as close to 3 cm from the wall, the surrounding walls and floor may get dirty. Please place the main unit at a distance from the wall.
The wall directly behind the air outlet may become dirty over time. When using the main unit for an extended period of time at the same location, periodically clean the walls adjacent to it.


FILTER GUIDELINES

- Follow the instructions in this manual for proper filter care and maintenance.
(page 12)

PART NAMES


MAIN UNIT

(FRONT)




1. Operation Panel
2. Air Outlet (Front/Back)
3. Cleanliness Monitor
4. Front Display
5. Main Unit
6. Handle (2 Locations)
7. Front Louver
8. Back Panel (Pre-Filter)
9. Air Inlet
10. Deodorizing Filter
11. HEPA Filter
12. Sensor (Internal) / Sensor Filter
Odor / Dust(sensitive)
13. Plasmacluster Ion Generating Unit
14. Unit Holder
15. Unit Cover
16. Unit Cleaning Brush
17. Power Cord, Plug

(BACK)




OPERATION PANEL

Press the button with "★" to start.



FRONT DISPLAY




1. **Power ON/OFF Button**
2. **AUTO Button, Indicator Light**
3. **HAZE Button, Indicator Light**
4. **Plasmacluster Ion SPOT Button, Indicator Light**
5. **MODE Button, Indicator Light**
6. **Timer Button**
(Press 3 sec.) **FILTER RESET Button**
7. **DISPLAY Button**
(Press 3 sec.) **CHILD-LOCK Button**
8. **Child-Lock Indicator Light**
9. **Light Sensor**
10. **HAZE/PM2.5 Monitor**
Indicates the Dust(sensitive) Sensor detects microscopic dust.
TURN OFF Orange Red
Clean ←————→ Impure
11. **Dust Monitor**
Indicates the Dust(sensitive) Sensor detects usual dust.
TURN OFF Orange Red
Clean ←————→ Impure

12. **Odor Monitor**
Indicates the Odor Sensor detects odors.
TURN OFF Orange Red
Clean ←————→ Impure
13. **Unit Replacement Indicator Light**
14. **Filter Replacement Indicator Light**
15. **ON Timer Indicator Light**
16. **OFF Timer Indicator Light**
17. **Plasmacluster Ion Light**
18. **DISPLAY**
 - **PM2.5 Monitor**
PM2.5 10µg/m³ to 499µg/m³ is displayed.
9µg/m³ or less Lo 34 Hi 500µg/m³ or more
 - **Wattage Monitor**
Indicates wattage by current operation.
 - **Timer Monitor**
Indicates setting time or remaining time of ON/OFF timer.
19. **Cleanliness Monitor**
Indicates the air purity of the room in5 levels with color changes.
Blue Yellow Red
Clean ←————→ Impure


PREPARATION

Always be sure to remove the power plug from the wall outlet.




FILTER INSTALLATION


1. Remove the Back Panel.




2. Remove the plastic bag from the each filter.



3. Install the filters in the correct order as shown.



4. Install the Back Panel.



NOTE


- When replacing the filter, making a memo of the start of use date is recommended.

OPERATION

START/STOP


START

STOP



AUTO MODE

The fan speed is automatically controlled depending on the 3 detection. (Dust(sensitive) / Odor / Light)



NOTE

- Front Display, Cleanliness Monitor automatically switch ON and OFF based on room brightness. (When light control is set to "Auto". (page 11))

HAZE MODE

Operates at HIGH fan speed for 60 minutes and then alternates between Low and High level for 20 minutes each.




10 minutes: Max High fan level
50 minutes: High fan level
20 minutes: Low fan level
20 minutes: High fan level

NOTE

- The Plasmacluster Ion can not be turned "OFF".

PLASMACLUSTER ION SPOT MODE

Use this mode when you want to remove adhering odor, germs, and other substances from cloths, sofas and curtains.




Adjust Front Louver manually.

NOTE

- Emits highdensity Plasmacluster Ions only in the forward direction.
- Discharges stronger air for 8 hours. When the operation finishes, the main unit will return to its prior operation mode.
- The Plasmacluster Ion can not be turned "OFF".

SELECTING MODE



SLEEP :

The main unit will operate quietly, and the fan speed is automatically switched depending on the amount of impurities in the air. The Front Display and Cleanliness Monitor go off automatically.


POLLEN :

The DUST SENSOR sensitivity is automatically increased and quickly detects impurities such as dust and pollen and clean the air powerfully.

ON TIMER

Select the length of time you want.
The Main Unit automatically starts once the selected time is passes.

(with the Main Unit OFF)





* Time can be set in from 10 minutes to 24 hours through the designated application.

OFF TIMER

Select the length of time you want.
The Main Unit automatically stops once the selected time is reached.


(with the Main Unit ON)



* Time can be set in from 10 minutes to 24 hours through the designated application.


CHILD LOCK

The operation of the operation panel will be locked.



SELECTING DISPLAY


(with the Main Unit ON)



PLASMACLUSTER ION ON/OFF

When the Plasmacluster function is ON, the Plasmacluster Ion light is on. (page 5)

(with the Main Unit ON)




HOW TO CHANGE VARIOUS SETTINGS

You can change the functions in the table "Type of setting" below.


1. Turn the Main Unit power OFF.



3. Select "Function number".
















4. Select "Setting number".




5. Press Power ON/OFF Button to finish the setting.



Function	Setting
Light Control You can select the brightness of the Front Display and Cleanliness Monitor. 	 Turn off *  Darker  Auto (default) Light automatically switches ON or OFF based on room brightness. Room is bright : light is ON Room is dark : light is OFF
Auto Restart If the Main Unit is unplugged or if there is a power failure, the Main Unit will resume operation with the previous settings after power is restored. 	 Cancellation  ON (default)
Adjusting Sensor Sensitivity (F3-F5)	
Light Sensor 	 Low
Dust(sensitive) Sensor 	 Standard (default)
Odor Sensor 	 High


* When set to "Turn off", the "Darker" light illuminates for 8 seconds after operation starts and then the light turns off.

CARE AND MAINTENANCE



MAIN UNIT / BACK PANEL

Wipe with a dry, soft cloth



Remove the dust gently with a cleaning tool such as a vacuum cleaner.

NOTE How to clean hard to remove dirt.


Back Panel

1. Add a small amount of neutral detergent to water and soak for about 10 minutes.

CAUTION


Do not apply excessive pressure when scrubbing the back panel.

2. Rinse off the neutral detergent with clean water.
3. Completely dry the filter in a wellventilated area.



Sensor Filter

1. Remove the Back Panel.
2. Remove the sensor filter.
3. If the sensor filter is very dirty, wash it with water and dry it thoroughly.




HEPA FILTER / DEODORIZING FILTER

Remove the dust on the filters.

CAUTION


Do not wash the filters. Do not expose to sunlight. (Otherwise these filters may lose efficacy.)

HEPA FILTER



Maintain only the tagged surface. Do not clean up the opposite surface. The filter is fragile, so be careful not to apply too much pressure.

DEODORIZING FILTER




Both surfaces can be maintained. The filter may be broken if being too much power is applied on it, so please handle it with care.

Some odors absorbed by the filters will break down over time, causing additional odors. Depending on usage conditions, and especially if the Main Unit is used in environments significantly more severe than a normal household, these odors may become noticeable sooner than expected.

Replace the filter in those cases or if dust is unable to be removed after maintenance.


Plasmacluster Ion Generating Unit (electrode section)

1. Remove the unit cover, and pull out the unit holder.




2. Remove dusts from the electrode section.

Unit Cleaning Brush



3. Insert the unit holder in the Main Unit, and install the unit cover.



CAUTION

- Do not clean with anything other than the unit cleaning brush. Doing so could lead to failures in the unit.
- A bent electrode could be cut off and dropped during the cleaning process, but it will not change the performance.
- Do not touch the electrode directly. Doing so could lead to pain/itching.
- Do not transform the electrode section. Doing so can damage it.
- Do not touch the connection terminals. Doing so can damage them.

REPLACEMENT

HEPA FILTER / DEODORIZING FILTER

LIFE OF FILTERS

Filter life varies depending on the room environment, usage conditions, and location of the Main Unit. Lifespan of HEPA filter and Deodorizing filter and replacement suggestions are based on purifying a room in which 5 cigarettes are smoked per day and the Main Unit's dust collection and deodorizing performance has declined to half the level of a new filter. We recommend replacing the filter more frequently if the Main Unit is used in conditions significantly more severe (PM2.5 etc.) than a normal household.

- HEPA Filter About 2 years after opening
- Deodorizing Filter About 2 years after opening

FILTER REPLACEMENT INDICATOR

When the filter replacement is needed soon, the filter indicator lamp start blinking. the blinking speed becomes faster once the timing comes.

Filter life varies depend on the operation mode.




Replace the Filter according to the instructions provided with the replacement filter. After performing replacement, reset the Filter Replacement Indicator.



Replacement Filter Model

Consult your dealer when purchasing a replacement filter.

HEPA Filter(1 unit)
FZ-J80HFE



Deodorizing Filter(1 unit)
FZ-J80DFE



Disposing of filters

Dispose of used filters according to local laws and regulations.

HEPA Filter material:

- Polypropylene
- Polyethylene



Deodorizing Filter material:

- Polypropylene
- Polyester
- Activated carbon

Plasmacluster Ion Generating Unit

UNIT REPLACEMENT INDICATOR

When the total operation time exceeds 17,500 hours, the Unit Replacement indicator will flash to indicate that the Plasmacluster Ion Generating Unit needs replacement.


Operating time 17,500 hours	Replace the Plasmacluster Ion Generating Unit
 Flash slowly	
19,000 hours	Stop the emission of the Plasmacluster ions.
 Flash quickly	

* The replacement time is not related to the selected operation mode.

Replacement Plasmacluster Ion Generating Unit Model

Consult your dealer when purchasing a replacement Plasmacluster Ion Generating Unit.

IZ-C90ME



Remove the claw of unit holder(①), and remove the Plasmacluster Ion Generating Unit(②).

Disposing of Plasmacluster Ion Generating Unit

Dispose of used Plasmacluster Ion Generating Unit according to local laws and regulations.

material:

- Polystyrene terephthalate
- electronic parts

TROUBLESHOOTING

Odor and smoke persists.

- Check the filters. If they appear to be extremely dirty, clean or replace them.

The Cleanliness Monitor is blue even when the air is not clean.

- The air may have been dirty when the main unit was plugged in. Unplug the main unit, wait one minute, and then plug the main unit in again.

The Cleanliness Monitor light is red even when the air is clean.

- Dirty or clogged dust(sensitive) sensor openings interfere with sensor operation. Gently clean the sensor filter or the back panel.

The Main Unit makes a clicking or ticking sound.

- The main unit may make clicking or ticking sounds when it is generating ions.

Air discharged from the Main Unit has an odor.

- Check to see if the filters are extremely dirty.
- Clean or replace the filters.

The Main Unit does not operate when cigarette smoke is in the air.

- Make sure the Main Unit is installed in a location in which the sensors can detect cigarette smoke.
- Check to see if the dust(sensitive) sensor openings are blocked or clogged. If they are blocked or clogged, clean the sensor filter or the back panel.

The FILTER Replacement Indicator Light is on.

- Whenever after performing replacing the filters, connect the power cord to an outlet and then press the Filter Reset Button. (page 13)

The Front Display is turned off.

- When Light control is set to "Auto", the light automatically turns off when the room is dark. Moreover, when Light control is set to "Turn off", the light is always off. If you do not want the light to be off, set Light control to the "Darker" setting. (page 11)

The Cleanliness Monitor changes color frequently.




- The Cleanliness Monitor automatically changes color when the dust(sensitive) sensor and odor sensor detect impurities. If you are concerned about the change, you can change sensor sensitivity. (page 11)

The Main Unit's Display does not match weather report.

- Outdoor and indoor as well as the home environment (the volume of traffic nearby, number of stories in home, etc.) may cause a reading different than those data.
- There is a difference in the level within the same room.

ERROR DISPLAY

If error occurs repeatedly, contact the Sharp Service Center.

	<ul style="list-style-type: none"> • The concentration of Plasmacluster ion is descending. ⇒ Maintain the Plasmacluster Ion Generating Unit (electrode section).
	<ul style="list-style-type: none"> • Is the the Plasmacluster Ion Generating Unit inserted properly? ⇒ Pull out the the Plasmacluster Ion Generating Unit and insert it to the end again, and then carry out the operation again.
	<ul style="list-style-type: none"> • Unplug the Main Unit, wait one minute, and then plug the Main Unit in again.

SPECIFICATIONS

Model	FP-J80M			FP-J60M		
Power supply	220-240 V 50-60 Hz					
Fan Speed Adjustment	MAX	MED	LOW	MAX	MED	LOW
Fan Speed (m ³ /hour)	480	288	60	396	222	60
Noise Level (dBA)	47	45	15	43	40	15
Rated Power (W)	48	28	4.0	38	18	3.6
Standby Power(W)	1.3			1.2		
Recommended Room Size (m ²) * ¹	~ 62			~ 48		
High density Plasmacluster ion recommended room size (m ²) * ²	~ 35			~ 26		
Cord Length (m)	2.0					
Dimensions (mm)	416 (W) × 291 (D) × 728 (H)					
Weight (kg)	10.6			10.0		

*1 • The recommended room size is appropriate for operating the main unit of maximum fan speed.

• The recommended room size is an area in which a given amount of dust particles can be removed in 30 minutes.

*2 • Room size in which approximately 25000 ions per cubic centimeter can be measured in the center of the room when the main unit is placed next to a wall, is running at MED mode settings, and is at a height of approximately 1.2 meters from the floor.

Standby Power

When the main unit's power plug is inserted in a wall outlet it consumes standby power in order to operate electrical circuits. To conserve energy, unplug the power cord when the main unit is not in use.

SHARP

SHARP CORPORATION

OSAKA, JAPAN